



<p><b>Article number:</b> 221 139 <b>Description:</b> <b>Module connecting cable - 2</b></p>	<p><b>Module connecting cable</b></p> <p>This <b>module connecting cable</b> can be used as a ready made solar cable for time-saving and secure connection of electrical operating materials under extreme mechanical and thermal loads.</p> <p>The UV-resistant solar cable has fitted <b>MC-T3 couplings</b> (3 mm plug system, socket/plug).</p> <p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Quick, cost-effective assembly</li> <li>• Simple installation</li> <li>• Stable, double-insulated solar cable</li> <li>• Protected against reverse polarization</li> </ul>
<p>Length: 2 m Content: 1</p>	
<p><b>Article number:</b> 221 140 <b>Description:</b> <b>Module connecting cable - 2/5</b></p>	
<p>Length: 2 m Content: 5</p>	
<p><b>Article number:</b> 221 141 <b>Description:</b> <b>Module connecting cable - 3</b></p>	<p><b>Solar cable</b></p> <p>Description: Heavy rubber sheathed cable H07RN-F Design: 1 x 4 mm<sup>2</sup> (single-wire) Colour: Black, red "TITANEX 11" imprint Insulation: Double wire insulation made from cross-linked elastomer</p> <p>External diameter: Min. 7.2 mm Max. 9.0 mm</p> <p>Weight: 94 g/m Strands: 48 x 0.33 mm (number x ø)</p> <p>Conductor resistance: 4.95 Ω/km (20 °C) Rated current: Max. 20 A (ambient temperature: +30 °C) Operating voltage: 750 V (laid loose) 1000 V (permanently placed)</p> <p>Operating temperature range: -60 °C to +85 °C permanently placed -35 °C to +85 °C laid loose</p> <p>Smallest permitted bending radius/cable diameter [d]: Permanently placed: 3 x d Laid loose: 6 x d Laid loose: 12 x d (&lt; -25 °C)</p> <p>Standards: DIN VDE 0282 HD 22 S 2 IEC 245-66</p>
<p>Length: 3 m Content: 1</p>	
<p><b>Article number:</b> 221 142 <b>Description:</b> <b>Module connecting cable - 3/5</b></p>	
<p>Length: 3 m Content: 5</p>	