



Article number: 221 139 Description: Module connecting cable - 2	Module connecting cable <p>This module connecting cable can be used as a ready made solar cable for time-saving and secure connection of electrical operating materials under extreme mechanical and thermal loads.</p> <p>The UV-resistant solar cable has fitted MC-T3 couplings (3 mm plug system, socket/plug).</p> <p>Features</p> <ul style="list-style-type: none"> • Quick, cost-effective assembly • Simple installation • Stable, double-insulated solar cable • Protected against reverse polarization
Length: 2 m Content: 1	
Article number: 221 140 Description: Module connecting cable - 2/5	
Length: 2 m Content: 5	
Article number: 221 141 Description: Module connecting cable - 3	<p>Solar cable</p> <p>Description: Heavy rubber sheathed cable H07RN-F</p> <p>Design: 1 x 4 mm² (single-wire)</p> <p>Colour: Black, red "TITANEX 11" imprint</p> <p>Insulation: Double wire insulation made from cross-linked elastomer</p> <p>External diameter: Min. 7.2 mm Max. 9.0 mm</p> <p>Weight: 94 g/m</p> <p>Strands: 48 x 0.33 mm (number x ø)</p> <p>Conductor resistance: 4.95 Ω/km (20 °C)</p> <p>Rated current: Max. 20 A (ambient temperature: +30 °C)</p> <p>Operating voltage: 750 V (laid loose) 1000 V (permanently placed)</p> <p>Operating temperature range: -60 °C to +85 °C permanently placed -35 °C to +85 °C laid loose</p> <p>Smallest permitted bending radius/cable diameter [d]: Permanently placed: 3 x d Laid loose: 6 x d Laid loose: 12 x d (< -25 °C)</p> <p>Standards: DIN VDE 0282 HD 22 S 2 IEC 245-66</p>
Length: 3 m Content: 1	
Article number: 221 142 Description: Module connecting cable - 3/5	
Length: 3 m Content: 5	