

<b>Article number:</b>
Description:

### 221 210 Flat-roof bracket-2 lsc/above

#### Contents:

#### 1 unit, each comprising

- L-shaped profile 40 x 25 x 4 mm (aluminium)
- Support profile 691 mm (aluminium)
- Support profile 713 mm (aluminium)
- Base profile (aluminium)
- M8 x 20 socket head screws (stainless steel)
- Serrated lock washers (stainless steel)
- M8 hexagonal nuts (stainless steel)
- Interlocking bolts (stainless steel)

# **Article number: Description:**

#### 221 211

### Flat-roof bracket.1-2 lsc/above

#### Contents:

## 1 unit, each comprising

- L-shaped profile 40 x 25 x 4 mm (aluminium)
- Support profile 863 mm (aluminium)
- Support profile 910.5 mm

### Flat-roof bracket-2 lsc/above

The flat-roof bracket 2 lsc/above, made of weather-resistant aluminium, is used in conjunction with mounting rails to install standard PV modules.

The collector is positioned at an angle of 30°.

Material: Plate finish aluminium, similar to RAL 7035

Flat-roof bracket-2 lsc/above Art. No. 221 210

For module size: 537 - 803 mm

Also required:

Securing cruciform kit, Art. No. 221 862

Flat-roof bracket 1-2 lsc/above Art. No. 221 211

For module size: 803 - 1000 mm

Also required:

Securing cruciform kit, Art. No. 221 081

# **Features**

- Weather-resistant aluminium
- Pre-assembled flat-roof bracket
- Quick and easy assembly
- Modular extension possible