



Article number: 221 517
Description: SB 3000-D

Input variables (DC)

Max. output	$P_{DC, max}$	3200 W
Voltage range	U_{PV}	268 – 600 V
Max. input voltage	$I_{PV, max}$	12 A
Max. no. of strings (parallel)		3
Separator	MC-T3 plug system	
Earth leakage protection		Yes
Reverse battery protection		Yes

Output values (AC)

Max. output	$P_{AC, max}$	3000 W
Power rating	$P_{AC, B}$	2750 W
Distortion factor	k	< 4 %
Voltage operating range	U_{AC}	198 – 260 V
Frequency range	f_{AC}	49.8 – 50.2 Hz
Short circuit stability		Yes
Mains connection	AC plug-in connector	
Max. efficiency	η_{max}	95.0 %
European efficiency level	η_{euro}	93.6 %
Power consumption (operational)		< 7 W
Power consumption (night-time operation)		0.25 W

Size (W x H x D)	434 x 295 x 214 mm
Weight	Approx. 32.0 kg
Protection (DIN EN 60 529)	IP65
Operating temperature range	-25 °C ... +60 °C

Operational data displayed:

- Current feed values
- Current voltage
- Overall yield
- No. hours operation to present
- Daily yield
- Fault
- Cause of fault

Inverter: SB 3000-D

The new modular system technology enables the direct current from the photovoltaic module to be converted into alternating current as early as possible in the energy supply chain. This eliminates the need for costly DC current distribution and the main DC leads that were previously necessary. The **SB 3000-D inverter** allows MPP control of up to three module groups (3 strings). The stand-alone power warning integrated in each string inverter means that (single-phase) connection is possible at any point along the 230 V mains supply.

Quality features, certificates

- Extremely efficient
- DC connection: MC-T3 plug-in system
AC connection: AC plug
- No photovoltaic current distribution required any more
- Integrated mains monitoring (VDEW regulations)
- Diagnosis and communication via the network:
PV voltage, mains voltage and mains frequency, feed supply and feed output, operating hours, energy supplied (kWh), operating mode.
- Protection class IP65, also suitable for external installation.
- Protection of installation and people through galvanic separation, insulation checking, excess voltage protection.
- CE mark
- PV installations are easy to extend thanks to modular construction.
- Module groups coupled at AC voltage level with tried-and-tested installation technology.
- Extended temperature range (-25 °C to +60 °C ambient temperature).
- Key operating data and faults displayed on a special cover.