



Article number: 231 452
Description: 5 OPzS 350

Battery voltage	2 V
Capacity C ₁₀ /1.80 V	370 Ah
Electrolyte density	1.24 kg/l
Cycle life at 50% depth of discharge	3000 cycles
Cycle life at 80% depth of discharge	1500 cycles
Weight of electrolyte	7.9 kg
Total weight with electrolyte	26.9 kg
Size (L x W x H)	208 x 126 x 535 mm

Article number: 231 453
Description: 6 OPzS 420

Battery voltage	2 V
Electrolyte density	1.24 kg/l
Capacity C ₁₀ /1.80 V	450 Ah
Cycle life at 50% depth of discharge	3000 cycles
Cycle life at 80% depth of discharge	1500 cycles
Weight of electrolyte	9.4 kg
Total weight with electrolyte	31.5 kg
Size (L x W x H)	208 x 147 x 535 mm

Article number: 231 454
Description: 7 OPzS 490

Battery voltage	2 V
Capacity C ₁₀ /1.80 V	520 Ah
Electrolyte density	1.24 kg/l
Cycle life at 50% depth of discharge	3000 cycles
Cycle life at 80% depth of discharge	1500 cycles
Weight of electrolyte	10.9 kg
Total weight with electrolyte	36.1 kg
Size (L x W x H)	208 x 168 x 535 mm

Batteries: 5 OPzS 350, 6 OPzS 420 and 7 OPzS 490

The Schüco 5 OPzS 350, 6 OPzS 420 and 7 OPzS 490 batteries are suitable for all static stand-alone and back-up solutions. The tubular plates ensure long and safe cycle operation.

Quality features, certificates

- Maximum cycle duration due to tubular/panzer plates
- Compatible when exchanged with existing systems
- Easy to check level of electrolyte
- Easy-to-clean surface
- Easy to use
- Corrosion-resistant pole design