



**Article number:** 231 455  
**Description:** 6 OPzS 600

Battery voltage	2 V
Capacity C <sub>10</sub> /1.80 V	610 Ah
Electrolyte density	1.24 kg/l
Cycle life at 50% depth of discharge	3000 cycles
Cycle life at 80% depth of discharge	1500 cycles
Weight of electrolyte	12.9 kg
Total weight with electrolyte	44.8 kg
Size (L x W x H)	208 x 147 x 710 mm

**Batteries: 6 OPzS 600, 8 OPzS 800 and 10 OPzS 1000**

The Schüco **6 OPzS 600, 8 OPzS 800 and 10 OPzS 1000** batteries are suitable for all static stand-alone and back-up solutions. The tubular plates ensure long and safe cycle operation.

**Quality features, certificates**

- Maximum cycle duration due to tubular/panzer plates
- Compatible when exchanged with existing systems
- Easy to check level of electrolyte
- Easy-to-clean surface
- Easy to use
- Corrosion-resistant pole design

**Article number:** 231 456  
**Description:** 8 OPzS 800

Battery voltage	2 V
Capacity C <sub>10</sub> /1.80 V	810 Ah
Electrolyte density	1.24 kg/l
Cycle life at 50% depth of discharge	3000 cycles
Cycle life at 80% depth of discharge	1500 cycles
Weight of electrolyte	16.9 kg
Total weight with electrolyte	61.3 kg
Size (L x W x H)	215 x 193 x 710 mm

**Article number:** 231 457  
**Description:** 10 OPzS 1000

Battery voltage	2 V
Capacity C <sub>10</sub> /1.80 V	1010 Ah
Electrolyte density	1.24 kg/l
Cycle life at 50% depth of discharge	3000 cycles
Cycle life at 80% depth of discharge	1500 cycles
Weight of electrolyte	21.1 kg
Total weight with electrolyte	74.6 kg
Size (L x W x H)	215 x 235 x 710 mm