



Article number: 231 455 Description: 6 OPzS 600		Batteries: 6 OPzS 600, 8 OPzS 800 and 10 OPzS 1000 The Schüco 6 OPzS 600, 8 OPzS 800 and 10 OPzS 1000 batteries are suitable for all static stand-alone and back-up solutions. The tubular plates ensure long and safe cycle operation. Quality features, certificates <ul style="list-style-type: none"> • Maximum cycle duration due to tubular/panzer plates • Compatible when exchanged with existing systems • Easy to check level of electrolyte • Easy-to-clean surface • Easy to use • Corrosion-resistant pole design
Battery voltage 2 V Capacity C ₁₀ /1.80 V 610 Ah Electrolyte density 1.24 kg/l Cycle life at 50% depth of discharge 3000 cycles Cycle life at 80% depth of discharge 1500 cycles Weight of electrolyte 12.9 kg Total weight with electrolyte 44.8 kg Size (L x W x H) 208 x 147 x 710 mm		
Article number: 231 456 Description: 8 OPzS 800		
Battery voltage 2 V Capacity C ₁₀ /1.80 V 810 Ah Electrolyte density 1.24 kg/l Cycle life at 50% depth of discharge 3000 cycles Cycle life at 80% depth of discharge 1500 cycles Weight of electrolyte 16.9 kg Total weight with electrolyte 61.3 kg Size (L x W x H) 215 x 193 x 710 mm		
Article number: 231 457 Description: 10 OPzS 1000		
Battery voltage 2 V Capacity C ₁₀ /1.80 V 1010 Ah Electrolyte density 1.24 kg/l Cycle life at 50% depth of discharge 3000 cycles Cycle life at 80% depth of discharge 1500 cycles Weight of electrolyte 21.1 kg Total weight with electrolyte 74.6 kg Size (L x W x H) 215 x 235 x 710 mm		