



<b>Article number:</b> 231 455 <b>Description:</b> 6 OPzS 600	<b>Batteries: 6 OPzS 600, 8 OPzS 800 and 10 OPzS 1000</b>  The Schüco <b>6 OPzS 600, 8 OPzS 800 and 10 OPzS 1000</b> batteries are suitable for all static stand-alone and back-up solutions. The tubular plates ensure long and safe cycle operation.  <b>Quality features, certificates</b> <ul style="list-style-type: none"> <li>• Maximum cycle duration due to tubular/panzer plates</li> <li>• Compatible when exchanged with existing systems</li> <li>• Easy to check level of electrolyte</li> <li>• Easy-to-clean surface</li> <li>• Easy to use</li> <li>• Corrosion-resistant pole design</li> </ul>																		
<table style="width: 100%; border-collapse: collapse;"> <tr><td>Battery voltage</td><td style="text-align: right;">2 V</td></tr> <tr><td>Capacity C<sub>10</sub>/1.80 V</td><td style="text-align: right;">610 Ah</td></tr> <tr><td>Electrolyte density</td><td style="text-align: right;">1.24 kg/l</td></tr> <tr><td>Cycle life at 50% depth of discharge</td><td style="text-align: right;">3000 cycles</td></tr> <tr><td>Cycle life at 80% depth of discharge</td><td style="text-align: right;">1500 cycles</td></tr> <tr><td colspan="2"> </td></tr> <tr><td>Weight of electrolyte</td><td style="text-align: right;">12.9 kg</td></tr> <tr><td>Total weight with electrolyte</td><td style="text-align: right;">44.8 kg</td></tr> <tr><td>Size (L x W x H)</td><td style="text-align: right;">208 x 147 x 710 mm</td></tr> </table>		Battery voltage	2 V	Capacity C <sub>10</sub> /1.80 V	610 Ah	Electrolyte density	1.24 kg/l	Cycle life at 50% depth of discharge	3000 cycles	Cycle life at 80% depth of discharge	1500 cycles			Weight of electrolyte	12.9 kg	Total weight with electrolyte	44.8 kg	Size (L x W x H)	208 x 147 x 710 mm
Battery voltage		2 V																	
Capacity C <sub>10</sub> /1.80 V		610 Ah																	
Electrolyte density	1.24 kg/l																		
Cycle life at 50% depth of discharge	3000 cycles																		
Cycle life at 80% depth of discharge	1500 cycles																		
Weight of electrolyte	12.9 kg																		
Total weight with electrolyte	44.8 kg																		
Size (L x W x H)	208 x 147 x 710 mm																		
<b>Article number:</b> 231 456 <b>Description:</b> 8 OPzS 800																			
<table style="width: 100%; border-collapse: collapse;"> <tr><td>Battery voltage</td><td style="text-align: right;">2 V</td></tr> <tr><td>Capacity C<sub>10</sub>/1.80 V</td><td style="text-align: right;">810 Ah</td></tr> <tr><td>Electrolyte density</td><td style="text-align: right;">1.24 kg/l</td></tr> <tr><td>Cycle life at 50% depth of discharge</td><td style="text-align: right;">3000 cycles</td></tr> <tr><td>Cycle life at 80% depth of discharge</td><td style="text-align: right;">1500 cycles</td></tr> <tr><td colspan="2"> </td></tr> <tr><td>Weight of electrolyte</td><td style="text-align: right;">16.9 kg</td></tr> <tr><td>Total weight with electrolyte</td><td style="text-align: right;">61.3 kg</td></tr> <tr><td>Size (L x W x H)</td><td style="text-align: right;">215 x 193 x 710 mm</td></tr> </table>	Battery voltage	2 V	Capacity C <sub>10</sub> /1.80 V	810 Ah	Electrolyte density	1.24 kg/l	Cycle life at 50% depth of discharge	3000 cycles	Cycle life at 80% depth of discharge	1500 cycles			Weight of electrolyte	16.9 kg	Total weight with electrolyte	61.3 kg	Size (L x W x H)	215 x 193 x 710 mm	
Battery voltage	2 V																		
Capacity C <sub>10</sub> /1.80 V	810 Ah																		
Electrolyte density	1.24 kg/l																		
Cycle life at 50% depth of discharge	3000 cycles																		
Cycle life at 80% depth of discharge	1500 cycles																		
Weight of electrolyte	16.9 kg																		
Total weight with electrolyte	61.3 kg																		
Size (L x W x H)	215 x 193 x 710 mm																		
<b>Article number:</b> 231 457 <b>Description:</b> 10 OPzS 1000																			
<table style="width: 100%; border-collapse: collapse;"> <tr><td>Battery voltage</td><td style="text-align: right;">2 V</td></tr> <tr><td>Capacity C<sub>10</sub>/1.80 V</td><td style="text-align: right;">1010 Ah</td></tr> <tr><td>Electrolyte density</td><td style="text-align: right;">1.24 kg/l</td></tr> <tr><td>Cycle life at 50% depth of discharge</td><td style="text-align: right;">3000 cycles</td></tr> <tr><td>Cycle life at 80% depth of discharge</td><td style="text-align: right;">1500 cycles</td></tr> <tr><td colspan="2"> </td></tr> <tr><td>Weight of electrolyte</td><td style="text-align: right;">21.1 kg</td></tr> <tr><td>Total weight with electrolyte</td><td style="text-align: right;">74.6 kg</td></tr> <tr><td>Size (L x W x H)</td><td style="text-align: right;">215 x 235 x 710 mm</td></tr> </table>	Battery voltage	2 V	Capacity C <sub>10</sub> /1.80 V	1010 Ah	Electrolyte density	1.24 kg/l	Cycle life at 50% depth of discharge	3000 cycles	Cycle life at 80% depth of discharge	1500 cycles			Weight of electrolyte	21.1 kg	Total weight with electrolyte	74.6 kg	Size (L x W x H)	215 x 235 x 710 mm	
Battery voltage	2 V																		
Capacity C <sub>10</sub> /1.80 V	1010 Ah																		
Electrolyte density	1.24 kg/l																		
Cycle life at 50% depth of discharge	3000 cycles																		
Cycle life at 80% depth of discharge	1500 cycles																		
Weight of electrolyte	21.1 kg																		
Total weight with electrolyte	74.6 kg																		
Size (L x W x H)	215 x 235 x 710 mm																		