



Article number: 231 458
Description: 12 OPzS 1200

Battery voltage	2 V
Capacity C ₁₀ /1.80 V	1210 Ah
Electrolyte density	1.24 kg/l
Cycle life at 50% depth of discharge	3000 cycles
Cycle life at 80% depth of discharge	1500 cycles
Weight of electrolyte	25.5 kg
Total weight with electrolyte	88.0 kg
Size (L x W x H)	215 x 277 x 710 mm

Batteries: 12 OPzS 1200 and 12 OPzS 1500

The Schüco 12 OPzS 1200 and 12 OPzS 1500 batteries are suitable for all static stand-alone and back-up solutions. The tubular plates ensure long and safe cycle operation.

Quality features, certificates

- Maximum cycle duration due to tubular/panzer plates
- Compatible when exchanged with existing systems
- Easy to check level of electrolyte
- Easy-to-clean surface
- Easy to use
- Corrosion-resistant pole design

Article number: 231 503
Description: 12 OPzS 1500

Battery voltage	2 V
Capacity C ₁₀ /1.80 V	1530 Ah
Electrolyte density	1.24 kg/l
Cycle life at 50% depth of discharge	3000 cycles
Cycle life at 80% depth of discharge	1500 cycles
Weight of electrolyte	34.2 kg
Total weight with electrolyte	114.3 kg
Size (L x W x H)	215 x 277 x 855 mm