



Article number: 231 934
Description: 12V AGM 60

Battery voltage	12 V
Capacity C ₁₀ /1.80 V	63.2 Ah
Electrolyte density	1.27 kg/l
Cycle life at 50% depth of discharge	1000 cycles
Cycle life at 80% depth of discharge	500 cycles
Total weight with electrolyte	26.5 kg
Size (L x W x H)	229 x 177 x 230 mm

Article number: 231 936
Description: 12V AGM 110

Battery voltage	12 V
Capacity C ₁₀ /1.80 V	111.1 Ah
Electrolyte density	1.27 kg/l
Cycle life at 50% depth of discharge	1000 cycles
Cycle life at 80% depth of discharge	500 cycles
Total weight with electrolyte	52 kg
Size (L x W x H)	498 x 177 x 230 mm

Article number: 231 937
Description: 12V AGM 140

Battery voltage	12 V
Capacity C ₁₀ /1.80 V	142.2 Ah
Electrolyte density	1.27 kg/l
Cycle life at 50% depth of discharge	1000 cycles
Cycle life at 80% depth of discharge	500 cycles
Total weight with electrolyte	54.5 kg
Size (L x W x H)	498 x 177 x 230 mm

Block batteries: 12V AGM 60, 12V AGM 110 and 12V AGM 140

Due to their absorption glass mat technology, the Schüco 12V AGM 60, 12V AGM 110 and 12V AGM 140 block batteries are suitable for both static and mobile use in conjunction with stand-alone systems.

Quality features, certificates

- Maintenance free
- Increased security against the risk of explosion through arc-back protection and central degasification.
- Easy-to-clean surface.
- Easy transport through integrated handle.