



Product Service

Compliance Document

No. D 18 04 85769 045

Holder of Certificate: **SolaX Power Network Technology (Zhejiang) Co., Ltd.**

No. 288 Shizhu Road,
Tonglu Economic Development Zone
311500 Tonglu City, Zhejiang Province
PEOPLE'S REPUBLIC OF CHINA

Product:

Converter
Grid-Connected Inverter

Model(s):

X1-Hybrid-5.0-D-E, X1-Hybrid-5.0-N-E, X1-Hybrid-4.6-D-E,
X1-Hybrid-4.6-N-E, X1-Hybrid-3.7-D-E, X1-Hybrid-3.7-N-E,
X1-Hybrid-3.0-D-E, X1-Hybrid-3.0-N-E, X1-Hybrid-5.0-D-C,
X1-Hybrid-5.0-N-C, X1-Hybrid-4.6-D-C, X1-Hybrid-4.6-N-C,
X1-Hybrid-3.7-D-C, X1-Hybrid-3.7-N-C, X1-Hybrid-3.0-D-C,
X1-Hybrid-3.0-N-C, X1-Fit-3.7C, X1-Fit-3.7E, X1-Fit-4.6C,
X1-Fit-4.6E, X1-Fit-5.0C, X1-Fit-5.0E

Parameters:

AC output ratings	
Nominal AC Voltage, Frequency:	230V~, 50/60Hz
AC input ratings	
Nominal AC Voltage, Frequency:	230V~, 50/60Hz
Battery Type:	Lithium
Battery operation voltage:	85-400VDC
Max. charge and discharge current:	20A
Max. charge and discharge power:	6000W
Operating ambient temperature range:	-20°C ... + 60°C
Ingress protection:	IP 65
Overvoltage category:	III (MAINS), II(DC)
Protection class:	I

Other ratings refer to attachments

Tested
according to:

EN 50438:2013/IS1:2015
(with national deviation setting of
Annex A: NL - Netherlands)

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. See also notes overleaf.

Test report no.: 704091628010-00

Date, 2018-04-20


(Zhengdong Ma)

Page 1 of 3





Product Service

Compliance Document

No. D 18 04 85769 045

Electrical ratings for various models:

Models	X1-Hybrid-5.0-D-E X1-Hybrid-5.0-N-E	X1-Hybrid-4.6-D-E X1-Hybrid-4.6-N-E	X1-Hybrid-3.7-D-E X1-Hybrid-3.7-N-E	X1-Hybrid-3.0-D-E X1-Hybrid-3.0-N-E
PV input				
Max. DC voltage:	600 V DC			
MPP voltage range:	125 – 550V DC			
Max. DC current (input A/input B):	10A/10A			
Isc PV (input A/input B):	14A/14A			
Max. DC power:	6000W	6000W	5000W	4000W
AC output				
Nominal AC voltage:	230V~			
Nominal AC frequency:	50/60Hz			
Max. Continuous AC current:	21.7A	21A	16A	14.4A
Nominal AC Apparent Power:	4999VA	4600VA	3680VA	3000VA
Power factor at rated power:	1			
Power factor range:	0.8 leading – 0.8 lagging			
AC input				
Nominal AC voltage:	230V~			
Nominal AC frequency:	50/60Hz			
Max. Continuous AC current:	21.7A	21A	16A	14.4A
Battery				
Battery type:	Lithium			
Battery Operation Voltage	85 – 400VDC			
Max. Charge and discharge current:	20A			
Max. Charge and discharge power:	6000W			
EPS output				
Nominal voltage:	230V~			
Nominal frequency:	50/60Hz			
Nominal apparent power:	5000VA	5000VA	4000VA	4000VA
EPS Rated current:	21.7A	21.7A	17.4A	17.4A

	X1-Fit-3.7E	X1-Fit-4.6E	X1-Fit-5.0E
AC output			
Nominal AC voltage	230V~		
Nominal AC frequency:	50/60Hz		
Max. Continuous AC current:	16A	21A	21.7A
Nominal AC Apparent Power:	3680VA	4600VA	49999VA
Power factor at rated power:	1		
Power factor range:	0.8 Leading – 0.8 Lagging		
AC input			
Nominal AC voltage:	230V~		
Nominal AC frequency:	50/60Hz		
Max. Continuous AC current:	16A	21A	21.7A
Battery			
Battery type:	Lithium		
Battery Operation Voltage	85 – 400VDC		
Max. Charge and discharge current:	20A		
EPS output			
Nominal voltage:	230V~		
Nominal frequency:	50/60Hz		
Nominal apparent power:	4000VA	5000VA	5000VA
EPS Rated current:	17.4A	21.7A	21.7A



Product Service

Compliance Document

No. D 18 04 85769 045

Models	X1-Hybrid-5.0-D-C X1-Hybrid-5.0-N-C	X1-Hybrid-4.6-D-C X1-Hybrid-4.6-N-C	X1-Hybrid-3.7-D-C X1-Hybrid-3.7-N-C	X1-Hybrid-3.0-D-C X1-Hybrid-3.0-N-C
PV input				
Max. DC voltage	600 V DC			
MPP voltage range:	125 – 550V DC			
Max. DC current (input A/input B):	10A/10A			
Isc PV (input A/input B):	14A/14A			
Max. DC power:	6000W	6000W	5000W	4000W
AC output				
Nominal AC voltage	230V~			
Nominal AC frequency:	50/60Hz			
Max. Continuous AC current:	21.7A	21A	16A	14.4A
Nominal AC Apparent Power:	4999VA	4600VA	3680VA	3000VA
Power factor at rated power:	1			
Power factor range:	0.8 leading – 0.8 lagging			
AC input				
Nominal AC voltage:	230V~			
Nominal AC frequency:	50/60Hz			
Max. Continuous AC current:	21.7A	21A	16A	14.4A
Battery				
Battery type:	Lithium			
Battery Operation Voltage	85 – 400VDC			
Max. Charge and discharge current:	20A			
Max. Charge and discharge power:	6000W			

	X1-Fit-3.7C	X1-Fit-4.6C	X1-Fit-5.0C
AC output			
Nominal AC voltage	230V~		
Nominal AC frequency:	50/60Hz		
Max. Continuous AC current:	16A	21A	21,7A
Nominal AC Apparent Power:	3680VA	4600VA	4999VA
Power factor at rated power:	1		
Power factor range:	0.8 Leading – 0.8 Lagging		
AC input			
Nominal AC voltage:	230V~		
Nominal AC frequency:	50/60Hz		
Max. Continuous AC current:	16A	21A	21,7A
Battery			
Battery type:	Lithium		
Battery Operation Voltage	85 – 400VDC		
Max. Charge and discharge current:	20A		