

Appendix to Certificate No: MCS IK0182 K2 Solar Mounting Solutions Limited

Issue: 1

Products

Model	Description	Reference No.
K2 SolidRail system	Pitched Roof Installation Kit (Above roof)	MCS IK0182/02
<i>Components</i>		
K2 SolidRail Light 37 (aluminium rail in lengths 2.1m, 3.43m, 4.35m, 6.1m)		
K2 SolidRail Light 37 Connector (aluminium, stainless steel, length 0.2m)		
K2 SolidRail Med 42 (aluminium rail in lengths 2.1m, 3.43m)		
K2 SolidRail Med 42 Connector (aluminium, stainless steel, length 0.2m)		
K2 Vario 1 Pan Tile Roof Fastener (design uplift resistance 961 N)		
K2 Vario 2 Pan Tile Roof Fastener (System test uplift 295 Pa per hook)		
K2 Fixed Pan Tile Roof Fastener (design uplift resistance 1109 N)		
K2 Flat Tile Roof Fastener (design uplift resistance 386 N)		
K2 Flat Tile Double Roof Fastener (design uplift resistance 64.5 N)		
K2 Rafter Screw SR (M10 x 180 / 200 / 250, design uplift resistance 1167 N)		
HECO Topix Timber Screw (stainless steel, 80 x M6, 80 x M8, 100 x M8)		
K2 T-Bolt 28/15 (stainless steel, 30 x M10)		
<i>Technical Information for the K2 SolidRail system</i>		
Roof substrate:	Timber rafters / purlins and metal purlins (sizes should be adequate to resist applied wind load and comply with building regulations)	
Minimum roof pitch:	15°	
Maximum design wind uplift:	3.94 kPa	
Value of partial safety factor:	1.1	

This certificate and appendix is maintained and held in force through periodic review and verification.

Signed for BRE Global Ltd.

Laura Critien
Programme Manager

17 April 2014
Date of Issue

17 April 2014
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd and is issued subject to terms and conditions (for details visit www.greenbooklive.com/terms).

To check the validity of this certificate please visit www.greenbooklive.com/check or contact us.

BRE Global Ltd., Garston, Watford WD25 9XX.
T: +44 (0)1923 664100 F: +44 (0)1923 664603 E: enquiries@breglobal.com

MCS is the Certification Mark for Onsite Sustainable Energy Technologies

